

Method for Adjusting a Lamp Relative to an Illuminating Beam Path
of a Microscope and a Microscope Suitable for
Carrying Out the Method

5 Field of the Invention

The invention relates to a method for adjusting a lamp relative to an illuminating beam path of a microscope without a beam homogenizer and a microscope suitable for carrying out the method.

10 Background of the Invention

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
220

an exchange of lamps) in such a manner that the microscope ensures a homogeneous illumination of the object field without manual intervention. On the other hand, experience has shown that especially routine users of microscopes are often unable to
5 ~~make a lamp adjustment in accordance with classical adjustment~~
criteria.

Beam homogenizers are used in illuminating devices for microlithographic apparatus and these illuminating devices ensure a homogeneous illumination of the mask to be imaged.

10 Additionally, the position of the light source relative to the illuminating beam path is adjusted to maximum light power of the beam homogenizer so that the light power emitted by the light source is optimally utilized.

It would be conceivable to utilize beam homogenizers also
15 for microscope illumination, for example, in the form of so-called fly-eye lenses or glass rods for mixing light. A homogeneous illumination of the object field would thereby be guaranteed independently of the positioning of the lamp relative to the illuminating beam path so that one could do completely
20 without a lamp adjustment. The use of such beam homogenizers would, however, lead to a complexity in microscopes which could not be realized.

Summary of the Invention

In view of the above, it is an object of the invention to
25 provide a simple method for lamp adjustment in microscopes which ensures a homogeneous illumination of the object field to be illuminated and is well suited to automatization. A further object of the invention is to provide a microscope which, when utilizing the method of the invention, is suitable to bring about
30 an adjustment of the lamp automatically which ensures a

homogeneous illumination of the object field.

The method of the invention is for adjusting a lamp unit relative to an illuminating beam path of a microscope devoid of a beam homogenizer in the illuminating beam path. The microscope includes: a microscope objective defining a pupil plane; an adjustable lamp unit for supplying the light transmitted along the illuminating beam path and a detector for detecting the light power of the transmitted light. The method includes the steps of: measuring the integral light power downstream of the pupil plane of the objective with the detector; and, adjusting the light unit relative to the illuminating beam path so that the light power detected by the detector is a maximum.

The invention is based on the recognition that a homogeneous illumination of the illuminated field is guaranteed also for illuminating beam paths without beam homogenizers when the areally integral light power behind the pupil plane of the microscope objective or behind the pupil plane of the illuminating beam path is a maximum with the operating conditions of the lamp being otherwise constant. Correspondingly, in the method according to the invention, the areally integral light power behind the pupil plane of the microscope objective or behind the pupil plane of the illuminating beam path is measured by a detector and the lamp body is so adjusted relative to the illuminating beam path that the integral light power, which is detected with the detector, is a maximum. What is here important is that the integral detection of the light power takes place only after passing through the diaphragm delimiting the light flow.

Based on the recognition of the invention, a simple adjustment criterion is provided which is exceptionally well

suited for the automated adjustment of the lamp after a lamp exchange or for the automated adjustment of the lamp in a first adjustment. The adjustment of the lamp can be motor controlled via software. The realization of the invention is, however, also
5 usable in the manual adjustment of the lamp because the adjustment criterion of a maximum integral light power can be checked much more simply by the inexperienced operator than the conventional adjusting criterion of a sharp imaging of a lamp arc in the objective pupil by means of a Bertrand lens.

10 A microscope, which is suitable for automatic lamp adjustment, includes motorized drives for adjusting the lamp relative to the illuminating beam path as well as an evaluation and control computer. The motorized drives operate to displace optical components in the illuminating beam path and this beam
15 path is without beam homogenizers. The evaluation and control computer sequentially controls the motorized drives for lamp adjustment in such a manner until a maximum of the integral light power is measured by a detector mounted behind the pupil plane of the illuminating beam path or of the microscope objective.

20 The detector for detecting the light power can be integrated into the illuminating beam path. In this case, it is advantageous when a reflecting region is provided on the specimen table of the microscope and when the detector detects the light reflected at the reflecting region. Alternatively, a portion of
25 the illuminating beam path can be reflected out onto a detector.

Furthermore, it is possible to provide the detector for detecting the light power more or less open on the specimen table. This embodiment is especially suitable for retrofitting already existing microscopes as well as for use of the invention
30 within already existing series of microscopes.

Th following are all suitable as a detector: an individual diode, a four-quadrant diode or even a CCD camera. In the case of a quadrant diode or a CCD sensor, the light power, which is detected with the individual sensor parts or sensor regions, is integrated over an area at the detector output. The use of a CCD sensor or a CCD camera is especially considered when, for example, a CCD camera is anyway provided for image documentation as, for example, in reflected light microscopes.

For applying the invention, the lamp can be adjusted either in three mutually orthogonal spatial directions relative to the illuminating beam path or, it is also possible, to adjust the lamp only in two mutually perpendicular spatial directions and a collector optic, which is arranged in the beam path, is displaceable along the optical axis of the remaining illuminating beam path.

A gradient method can preferably be used for locating the maximum light power. In such a gradient method, and starting from an initial position, the maximum gradient of the light power is determined in dependence upon a position change of the lamp relative to the illuminating beam path and/or the lamp and the collector optic relative to the illuminating beam path and, thereafter, the lamp and/or the collector optic is shifted in the direction of the maximum gradient of the light power in the illuminating beam path.

Brief Description of the Drawings

The invention will now be described with reference to the drawings wherein:

FIG. 1 is a reflected light microscope, in section, having a detector integrated in the specimen table;

FIG. 2 is a flowchart of the process steps which are run

through with the automated lamp adjustment in a microscope;

FIG. 3 is a flowchart of the process steps which are run in the gradient method for locating the maximum light power; and,

FIG. 4 shows a microscope, in section, having a detector integrated into the illuminating beam path.

Description of the Preferred Embodiments of the Invention

In FIG. 1, the upper part of the microscope stand with the illuminating beam path accommodated therein is identified by reference numeral 1. A specimen table 2 adjustable in elevation for focusing is accommodated on the microscope in a manner known per se. Furthermore, the microscope includes a lens turret 3 containing objectives 4 of which only one is shown in FIG. 1.

The reflecting illuminating beam path in the microscope of FIG. 1 includes, in principle, the components which are usual for the adjustment of the Köhler illuminating conditions. A halogen lamp or a gas discharge lamp 5 can be provided as a light source. The light, which is emitted by the lamp 5, is collimated by a collector lens 9 and, if required, is collimated in combination with a collector mirror 17 which collects the backward radiated light and reflects it back into the lamp 5. A field diaphragm 10 is provided in the region of the collimated beam path and is adjustable with respect to its aperture diameter. The field diaphragm 10 is arranged conjugated to the focal plane of the microscope objective 4. A lens 11 is mounted downstream of the field diaphragm 10 and images the field diaphragm 10 to infinity. A second diaphragm 12 is provided in the focal plane of lens 11 for adjusting the illumination aperture. The second diaphragm 12 is adjusted with respect to its aperture diameter and is imaged to infinity by a downstream lens 13 and, after being reflected into the viewing beam path, the aperture diaphragm 12 is imaged

into the exit pupil 18 of the microscope objective 4 by the tube lens 15 via a beam splitter 14. The tube lens 15 is in the common part of the illuminating and viewing beam path.

A large area diode 16 is integrated as a detector in the specimen-table 2 of the microscope. With the diode 16, the total light intensity focused by the microscope objective 4 is detected. This diode 16 can be configured as a simple large-area diode. However, it is especially advantageous to configure the diode 16 as a four-quadrant diode. In this last case, this diode 16 can thereby simultaneously function to also calibrate the specimen table in that the center point of the four-quadrant diode defines the origin of the axes as a reference point, for example, as zero point for the X/Y adjustment of the specimen table.

The diameter of the light-sensitive area of the diode 16 is at least as large as the diameter of the field illuminated in the focal plane of the objective 4. In a quadrant diode, the diameters of the four quadrants together are taken as the diameter.

For realizing an automated lamp adjustment, the receptacle or holder 8 of the lamp 5 is adjustable by two motorized drives (6, 7) in the two directions perpendicular to the optical axis 19 of the illuminating beam path. The collector lens 9 is displaceable in the direction of the optical axis 19 by a further motorized drive 20. Alternatively to a displacement of the lamp 5 as well as the collector lens 9, the lamp 5 can also be displaceable via three appropriate drives in the three mutually perpendicular spatial directions. However, for this purpose, a correspondingly more complex mechanism is required because of the degrees of freedom which would be required for an adjustment in

the three mutually perpendicular directions independently of each other.

Position sensors provide input signals representing the end positions of the drives (6, 7, 20) so that information is provided to a computer 22 as to the actual positions reached by the respective drives (6, 7, 20). Alternatively, the drives (6, 7, 20) can be step motors so that the distance to be moved is known from the number of steps to be executed.

The adjusting drives (6, 7) of the lamp 5 and the adjusting drive 20 of the collector lens 9 are drivable by the control computer 22 across an interface 21. The output signals of the diode 16 are supplied to the control computer 22 over the same interface 21.

The method steps, which are run through for an automatic lamp adjustment, are explained in greater detail in the following with respect to FIG. 2. The adjusting process begins with an initial step 30 which is, for example, triggered in that the user confirms a completed exchange of lamps via a key pad. In a next initialization step 31, the specimen table 2 is moved in the direction of the optical axis of the microscope objective 4 as well as in the two directions perpendicular thereto so that the diode 16 is positioned beneath the microscope objective 4 and, as a consequence, detects the total light power, which is collected by the microscope objective 4. This initialization can, of course, take place also automated if the microscope has a motorized focusing drive and a motorized X/Y table. In this case, the control and evaluation computer 22 correspondingly controls the motorized drives for the focusing and the lateral position of the specimen table. If no motorized drives for the focusing and the X/Y table are provided, then the user receives

the command via the key pad to so adjust the specimen table that the diode 16 is positioned directly beneath the objective 4.

In the next two steps (32, 33), an assignment of a variable takes place wherein the value of a variable "new position" is

5 ~~assigned to a variable "old position" and the value of a variable~~
~~"position a" is assigned to the variable "new position". For the~~
first-time runthrough of the process, fixed pregiven values are
utilized for these variables in the initialization step 31. In a
next step 34, the drives (6, 7) of the lamp and the drive 20 of
10 the collector lens are so driven that the drives assume the
values of the variable "new position". Thereafter, a measurement
of the light power takes place with the diode 16 and a readout of
the measured light power takes place as well as, subsequently, in
a step 35, a further variable assignment takes place in that the
15 value of the measured light power is assigned to a variable
"light power of new position". In a next step 36, a decision
inquiry takes place as to whether the value of the variable
"light power of old position" (which likewise was assigned a
value in the initialization step) is less than the value of the
20 variable "light power of new position". In the event this
question is answered in the negative, then, in a step 37, a
variable "actual step width" is assigned the value of a variable
"countdown" and in a next step 38, the variable "light power of
new position" is assigned the value of the variable "light power
25 of old position". In a next step 39, the value of a variable
"position a" is computed as the sum of the variable "old
position" and the product of the value of the variable "actual
step width" and the variable "derivative of light power". In a
next decision step 40, a check is made as to whether the value of
30 the variable "actual step width" is greater than a pregiven limit

value.. If this inquiry is answered in the affirmative, then the routine jumps with the new values back to the above step 32 so that the subsequent steps are run through anew. If, in contrast, the inquiry in step 40 is answered with "false", then the end of the routine is reached.

If, in the above-described step 36, the inquiry as to whether the value of the variable "light power of old position" is less than or equal to the value of the variable "light power of new position" is answered in the affirmative, then, in step 41, the variable "actual step width" is assigned the value of a variable "count up" and, thereafter, in step 42, the gradient of the light power is measured. The details with respect to the measurement of the gradient of the light power are described below with respect to the sequence diagram in FIG. 3. After the measurement of the gradient of the light power, the value of the measured gradient is assigned to the variable "derivative of light power" and, thereafter, in step 43, the value of the sum of the variables "new position" and the product of the variables "actual step width" and "derivative of light power" is assigned to the variable "position a". Thereafter, the routine arrives also via this branch at the inquiry 40 as to whether the value of the variable "actual step width" is greater than a limit value, and, in the case that this inquiry is answered in the negative, the routine arrives at the end of the routine and, in the case that this question is answered in the affirmative, the routine also in this case returns to step 32 downstream of the initialization step 31.

A method for determining the gradient of the light power is described in greater detail in the following with respect to FIG. 3. In two first assignment steps, the value of the variable

"light power" is assigned to the variable "actual light power" and the value of the variable "new position" is assigned to the variable "actual position". The values of these variables are either known from the previously run steps in accordance with

5 FIG. 2 or are determined in the initialization step 31 according to FIG. 2. In two further initialization steps (53, 54), the values of the index variables (i) and (N) are determined.

Thereafter, each individual drive (6, 7) of the lamps and the drive 20 of the collector lens is sequentially displaced by a
10 pregiven step width d_i and the light power impinging in each case on the diode 16 is measured in a step 55. In a next step 56, the change of the light power is measured, that is, the difference of the variable "light power" and the variable "actual light power" is computed. These steps are carried out for all three drives
15 separately one after the other. After the difference values of the light power for the drive is present for all three drives, the gradient of the light power (that is, a value of the variable "derivative of light power") is computed in step 37 as a vectorial quantity. The value of the vectorial quantity
20 "derivative of light power" which was so computed is then used in steps 39 and 43 to compute the new position "position a" which is to be controlled to.

In FIG. 4, a microscope according to the invention is shown having a transmitted-light illumination. Those components in the
25 embodiment of FIG. 4, which correspond to the components in the embodiment of FIG. 1, each have the same reference numeral increased by 100. The light, which is emitted by a lamp 105, is collimated by a collector lens 109 and a collector mirror 117. A diaphragm 110 follows the collector lens 109 and is variable with
30 respect to its aperture diameter. With respect to the downstream

optic, the diaphragm 110 is arranged so as to be conjugated to the focal plane of the objective 104 and functions to adjust the illuminated field. A lens 111, which follows the field diaphragm 110, generates an image of the light source of the lamp 105 in the plane of an aperture diaphragm 112. At the same time, the lens 111 images the field diaphragm 110 to infinity. Two further lenses (113, 115) follow behind a deflecting mirror 114. On the one hand, the two additional lenses (113, 115) together image the plane of the aperture diaphragm 112 in the rear focal plane of the transmitted-light condenser 125 and, simultaneously, image the field diaphragm 110 to infinity. The transmitted-light condenser 125 is integrated into the specimen table 102. A so-called Köhler illumination can be adjusted in this embodiment in a manner known per se by adjusting the aperture diameters of the field diaphragm 110 and the aperture diaphragm 112.

A partially transmitting mirror 123 is arranged rearward of the aperture diaphragm 112 for detecting the integral light power within the illuminating beam path. A small portion of the illuminating light is coupled out via the mirror 123 and is focused via a downstream lens 124 on a diode 116 integrated into the base of the microscope.

In this embodiment too, the lamp 105 is motorically adjustable in two mutually perpendicular directions perpendicular to the optical axis 119. For this purpose, the motorized drives (106, 107) are provided. Furthermore, also in this embodiment, the collector lens 109 is adjustable via a motor drive 120 in the direction of the optical axis 119 for adjusting the illumination. The drive of the drive motors (106, 107) for adjusting the lamp 105 and the drive of the drive 120 for the

axial displacement of the collector lens 109 again takes place via a control computer 122 as well as via an interface 121, which is provided on the microscope stand. The output signal of the diode 116 is supplied to the control computer 122 also via the interface 121.

In the embodiment of FIG. 4 having the diode 116 integrated into the illuminating beam path, it is significant for the adjustment of the lamp 105 in accordance with the method described with respect to FIGS. 2 and 3 that the position of the aperture diaphragm 112 is conjugated to the position of the entry pupil of the condenser 125 and, with respect to its aperture diameter, corresponds to the pupil diameter of the condenser 125 while considering the magnification or demagnification effected by the two lenses (113, 115). Requirements of this kind are not present in the embodiment of FIG. 1; however, it is there necessary that the diameter of the light-sensitive region of the diode 116 is greater or equal to the diameter of the illumination field illuminated by the objective 4.

The method according to the invention described above can, of course, be utilized not only for the adjustment of the lamp (5, 105) relative to the illuminating beam path but, for a first adjustment, can also be used to adjust the collector mirror (17, 117) relative to the collector (9, 109). For this purpose, the lamp and the concave mirror can be iteratively adjusted alternately to maximum power at the diode (16, 116). After a coarse preadjustment of the collector mirror, approximately three or four iterations are necessary in order to achieve an optimal adjustment. Thereafter, when there is an exchange of lamps, only the lamp is adjusted perpendicular to the optical axis and the collector lens (9, 109) is adjusted in the

direction of the optical axis. An adjustment of the collector mirror (17, 117) is later not necessary when there is an exchange of lamps.

5 The method of the invention was described above with respect to the gradient method for determining the position of the lamp with maximum light power. The gradient method affords the advantage that it can, on the one hand, be implemented simply and, on the other hand, leads to an optimal adjustment with relatively few iteration steps. In lieu of a gradient method,
10 other algorithms are, however, conceivable, for example, algorithms with which the individual drives are each driven sequentially until each individual direction of movement reaches the maximum of light power and these steps are repeated sequentially a number of times until the absolute maximum as to
15 detected light power is achieved.

It is understood that the foregoing description is that of the preferred embodiments of the invention and that various changes and modifications may be made thereto without departing from the spirit and scope of the invention as defined in the
20 appended claims.